





Solus Boom Barriers

Combination of Reliability, Performance and Elegant looks, Solus Boom Barriers are fitted with high quality maintenance free, powerful electro mechanical AC driven mechanism. Forming a core part of barrier this drive mechanism and motor base is Precision Die casted with aluminum alloy. This mechanism along with balanced spring provides soft, no noise & no jerk operations even in intensive usage. This also ensures prolonged working life for Barrier.

Boom Length can be chosen from 2 to 6 meters, accordingly the barrier closing time varies from 2 to 4 seconds. They can be conveniently installed at right or left hand side of Vehicle entrance. A manual clutch option is provided to open the Boom Barrier in power outage situations.

Key Features:

- 2 to 6 meter length. 1 second Per Meter Opening, Closing time.
- No maintenance, No noise motor.
- Key & Hand Clutch options for manual operation.
- Dual Boom limiting methods.
- Integrable with LED signals & Time display units.





Ordering Information

Technical Specifications		
	S DBA 600	S DBA 900
Motor	AC	AC
Working Cycle	50%	50%
Power Supply	220V	220 +- 10% V
Rated Power	120 W	120 W
Opening Time	2-4 Sec	2-4 Sec
Boom Length	upto 6 meters	upto 4.5 Meters
Dimensions	360mm*240mm*1140mm	360mm*240mm*1140mm
Working Temperature	-40 to 75 deg C	-40 to 75 deg C
Humidity	0 to 90 %	0 to 90%

How to Order	
Model No	Description
S DBA 600	Solus Boom Barrier with Boom Length upto 6m
S DBA 900	Solus Boom Barrier with Boom Length upto 4.5m
Accessories	
S DBA 180	Loop Detection Assembly
S DBA 170	Remote Control







Solus Security Systems Pvt. Ltd.

S. V. Road, Goregaon (W) Mumbai 400104 Subramanyapura Post, Bangalore – 560 061 India.

202, Shivam Chambers, Next to Sahara | # 5, 3rd Floor, Uttarahalli Main Road